

## KÄRCHER B 40 C Bp

Battery-powered walk-behind scrubber dryers in the 40 litre class without traction drive, ideal for areas of 400 to 1100 m<sup>2</sup>. With innovative KIK system, roller or disc brush head.

The B 40 C Bp battery-powered walk-behind scrubber drier can be optionally equipped with roller brush head with parallel roller brushes and sweeping function or with disc brush head. It is ideal for easy, safe and convenient handling, also without traction drive. The new KIK system offers reliable protection against incorrect operation. The machine is standard with a curved squeegee

This scrubber drier can also be fitted with a number of other useful optional features. For example with the Home Base "Mop" or "Box" kits for better transport of additional utensils or with "Auto Fill-in" for simple filling of the fresh water tank and tank rinsing system for simplified rinsing out of the dirty water tank. Innovative Kärcher accessories, e. g. brushes with various degrees of hardness, different squeegee blades, pad driver plates/roller pad shaft and pads make this scrubber drier ideal for a wide range of cleaning tasks.

### Features:

#### *EASY Operation*

- Simple to use.
- The basic functions are controlled with the EASY switch.

#### *ecoefficiency*

- For significantly reduced energy consumption and substantially longer battery runtime.
- The eco!efficiency mode is very quiet and thus optimal for noise-sensitive areas (e.g. hospitals or hotels).

#### *Straight or curved squeegee*

- For perfect suction on every floor.
- There are also different squeegee blades to choose from: natural rubber or oil-resistant polyurethane, slotted squeegees for sensitive floors or closed for rough floors.

#### *Innovative KIK system*

- Yellow key for operators, grey key for supervisors.
- Reduced service costs due to less operating errors.

#### *Practical device shape*

- The slim machine can be easily manoeuvred, even in tight spaces.
- The asymmetric shape offers the best view of the surface to be cleaned.

### Standard Features / Accessories

Tank-in-tank system

B 40 C with roller brush options:

#### **R 45 (2.763-020.0)**

Brush working width	450 mm
Working width, suction	850 mm
Theoretical area performance	1,800 m <sup>2</sup> /h

#### **R 55 (2.763-013.0)**

Brush working width	550 mm
Working width, suction	850 mm
Theoretical area performance	2,200 m <sup>2</sup> /h



B 40 C with disk brush options:

**D 43 (2.763-023.0)**

Brush working width 430 mm  
Working width, suction 850 mm  
Theoretical area performance 1,700 m<sup>2</sup>/h

**D 51 (2.763-026.0)**

Brush working width 508 mm  
Working width, suction 850 mm  
Theoretical area performance 2,000 m<sup>2</sup>/h



**Part no. 0.300-035.0**

**TECHNICAL SPECIFICATIONS**

Dimensions (L x W x H)	1209 x 498 x 1145 mm
Working width, brush	430 mm
Brush working width	550 mm
Working width, vacuum	850 mm
Motor rating	up to 1100 W
Battery	24 V
Container contents: fresh water	40 l
Container contents: wastewater	40 l
Weight (without battery)	60 kg

